

AT-CTV-IPD04MLMSC

IP Dome Camera



AT-CTV-IPD04MLMSC is a 4MP IP dome camera designed for high-quality video surveillance in various environments. With smart video analytics, human and vehicle detection, and infrared night vision up to 30 meters, it ensures clear and secure monitoring day and night. Supporting True WDR, 3DNR, HTTPS, ONVIF, and

Features

- **IR distance up to 30 meters**
- **Video Analysis(area intrusion, absent alarm, loitering, line, crossing detection, vehicle illegal parking, retrograde detection)**
- **Built in human/vehicle detection algorithm, carry out human/vehicle detection independently**
- **Detection frame 5fps, detect 5-10 people at the same time**
- **Support 3DNR and True WDR 140dB**
- **Support HTTPS transmission with password**
- **Support ONVIF, SLINK, Email, NTP service**
- **Support SECVIEW Mobile Application, Lite IMS and Professional IMS 4.0 central management software**

Technical Specification

Power Supply	DC12V, 0.5A, max. 5W; PoE: 802.3af, Max. 6W
Sensor	1/2.7" Progressive scan CMOS sensor
Lens	2.7-13.5mm Motorized
Lens interface	M14
Focal Length & FOV	Horizontal FOV 113°(W)-31.4°(T), vertical FOV 58.4°(W)-17.6°(T), diagonal FOV 138.2°(W)-36°(T)
Min. Illumination	Color: 0.001Lux/F1.6, AGC ON, B/W: 0Lux (IR LED ON)
Electronic Shutter	1/5 s to 1/100,000 s
S/N Ratio	≥ 52 dB
Day/Night mode	Auto, Day, Night, Custom
IR Distance	25-30m/18x IR Array Leds
WDR	WDR 140dB(off/low/middle/high)
Image Setting	Brightness, Contrast, Sharpness, Saturation, Chroma
IR Led Control	Auto/Manual/Off
DNR	Off/low/middle/high/higher
Defog	Off/low/middle/high
Track People	Support
Max Detection People	5-10 people at the same time
Max Detection Frame	5fps/s
Video Encode Standard	Smart H.265/H.265/H.264
Encoding Feature	4MP(2560*1440)/3MP(2304*1296)/2MP(1920*1080) 25fps
Audio Standard	G.711u / G.711A 64Kbps
Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP
Connexion Protocol	ONVIF, SLINK, HIK, TST
Security Mode	Authorized username & password, HTTPS w/ password, AES connecting w/ password, RTSP verification
Network Port	RJ45 10M/100M network self adjustable
Audio	Microphone
Protection	Vandalproof IK10
Working Temp	-30°C ~ 60°C
Working Humidity	0% ~ 90%
Dimension	112.2mm(D) x 100.8mm(H)