

AT-CTV-IPB06FLMS

IP Bullet Camera

DESCRIPTION

AT-CTV-IPB06FLMS is a 6MP outdoor IP bullet camera designed for sharp image capture and reliable performance in outdoor environments. With human detection, infrared night vision and smart video features, it provides clear, continuous monitoring for spaces like offices, shops, and residential areas.



MAIN PRODUCT

- 6MP
- Detection frame 5fps, detect 5 people at the same time
- Support low bit rate and low latency
- Smart IR mode: Dual lights, warm light, Infrared led, dual lights to get full color image when detect human at night
- Support ICR auto switch, realize D&N surveillance
- Support 3D DNR and digital WDR
- Support auto-electronic shutter to suit different surveillance environment
- Support HTTPS transmission with password
- Change the password when the initial device is started to ensure the password security

TECHNICAL SPECIFICATION

<i>Power Supply</i>	DC12V, 0.5A, max. 5W; PoE: 802.3af, Max. 6W
<i>Sensor</i>	1/2.9" Progressive scan CMOS sensor
<i>Lens</i>	3.6mm
<i>Lens interface</i>	M12
<i>Min. Illumination</i>	Color: 0.005Lux/F1.6, AGC ON, B/W: 0Lux (IR LED ON)
<i>Electronic Shutter</i>	1/5 s to 1/100,000 s
<i>S/N Ratio</i>	≥ 52 dB
<i>Day/Night mode</i>	Auto, Day, Night, Custom
<i>Dual lights</i>	Warm light 25m, Infrared IR 30m

TECHNICAL SPECIFICATION

<i>Image Setting</i>	Brightness, Contrast, Sharpness, Saturation, Chroma
<i>IR Led Control</i>	Auto/Manual/Off
<i>Track People</i>	Support
<i>Max Detection People</i>	≤5 people humanoid
<i>Humanoid Size</i>	Humanoid Pixel ≥40x40
<i>Capture Speed</i>	≤1s
<i>Max Detection Frame</i>	5fps/s
<i>Video Encode Standard</i>	S.265/H.265/H.264
<i>Encoding Feature</i>	6MP, 4MP, 3MP, 2MP
<i>Video Type</i>	Composited stream/video stream
<i>Audio Standard</i>	G.711u/64Kbps
<i>Protocol</i>	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, RTP, IPv4, DDNS, NTP, PPPOE, UPNP, SMTP, DNS, QoS
<i>Connetion Protocol</i>	ONVIF, SLINK
<i>Security Mode</i>	Authorized username & password, HTTPS w/ password, AES connecting w/ password, RTSP verification
<i>Network Port</i>	RJ45 10M/100M network self adjustable
<i>Audio</i>	Microphone, Speaker built in
<i>Protection</i>	IP67, Metal
<i>Working Temp</i>	-30°C ~ 60°C
<i>Working Humidity</i>	0% ~ 90%
<i>Dimension</i>	168.45mm(L) x 67.40mm(W) x 65mm(H)