

AT-CTV-IPD04P360M

IP Fisheye Camera

DESCRIPTION

AT-CTV-IPD04P360M is a 4MP, fisheye IP camera offers wide-angle panoramic coverage with flexible resolution and frame rates.



MAIN PRODUCT

- 4MP/3MP@20fps, 2MP@25fps
- Detection frame 5fps, detect 5 people at the same time
- Support low bit rate and low latency
- Smart H.265/H.265/H.264, save bandwidth and storage space
- IR distance up to 20m
- Support ICR auto switch, realize D&N surveillance
- Support 3D DNR and digital WDR
- Support auto-electronic shutter to suit different surveillance environment
- Support HTTPS transmission with password
- Support ONVIF, SLINK, email, NTP service
- Change the password when the initial device is started to ensure the password security

TECHNICAL SPECIFICATION

<i>Power Supply</i>	DC12V, 0.5A, max.5W PoE:302.3af, Max.6W
<i>Sensor</i>	1/2.8" Progressive scan CMOS sensor
<i>Lens</i>	1.7mm
<i>FOV Length & FOV</i>	2.8mm, horizontal FOV 102.6°, Vertical FOV 56.4°,diagonal FOV 122° 3.6mm, horizontal FOV 82.3°, Vertical FOV 44.7°,diagonal FOV 97.4°
<i>Min. Illumination</i>	0.001Lux@F1.6, AGC ON B/W: 0Lux (IR LED ON)
<i>Electronic Shutter</i>	1/5 s to 1/100,000 s
<i>S/N Ratio</i>	≥52dB

TECHNICAL SPECIFICATION

<i>Day/Night mode</i>	Auto, Day, Night, Custom
<i>IR distance</i>	10-20m
<i>D-WDR</i>	D-WDR (off/low/middle/high)
<i>DNR</i>	Off/low/middle/high/higher
<i>Detection Quantity</i>	≤5 people humanoid
<i>Video Encode Standard</i>	S.265/H.265/H.264
<i>Encode Feature</i>	Main Stream: 4MP 2650x1440@20fps, 2MPP 1920x1080@25fps Sub code stream: D1(720*576), VGA(640*360)
<i>Video Code Rate</i>	Fixed code rate, variable code rate (Main stream code: 160Kbps 4000Kbps)
<i>Audio Standard</i>	G.711-u/64Kbps
<i>Built-in Mic</i>	Yes
<i>Built-in Speaker</i>	Ye Two-way audio
<i>Human Detection</i>	Yes
<i>Led</i>	2pcs warm-light Led + 2pcs IR Led
<i>Distance</i>	20-30M
<i>Protocol</i>	HTTP/RTSP/FTP/SMTP/DHCP/NTP/ NFS, etc.
<i>P2P</i>	Yes
<i>Network Port</i>	1-RJ45, 100Mbps, POE optional
<i>Working Temp</i>	-30°C ~ 60°C
<i>Working Humidity</i>	10% ~ 90%
<i>Dimension</i>	120mm(D) x 35mm(H)