

AT-CTV-NV36TB16S4

Network Video Recorder

DESCRIPTION

AT-CTV-NV36TB16S4 is a high-performance 36-channel Network Video Recorder designed for modern IP-based CCTV systems. With real-time monitoring, remote access via mobile app or browser, and a user-friendly interface, it is ideal for medium to large-scale surveillance setups requiring secure and centralized video management.



MAIN PRODUCT

- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- 4 SATA hard disk up to 16TB
- 2 RJ45 1000M network interface
- Smart analysis: Human detection, line crossing, retrograde detection, absent detection, loitering detection, area intrusion, illegal vehicle parking
- Electronic amplification on preview and playback image
- Support to configure and maintain IP camera under slink protocol
- Support ANR function(need front IP camera support TF card storage)
- Support broadcast function

TECHNICAL SPECIFICATION

<i>Power Supply</i>	DC12V/8A
<i>Power Consumption</i>	<60W
<i>IP Camera Input</i>	36 Channel
<i>Incoming Bandwith</i>	512 Mbps
<i>Outgoing Bandwith</i>	256 Mbps
<i>HDMI Output</i>	3840x2160, 1920x1080, 1280x1024, 1024x768
<i>VGA Output</i>	1920x1080, 1280x1024, 1024x768

TECHNICAL SPECIFICATION

<i>Decoding Capacity</i>	1ch 8MP, 4ch 2MP, 36ch D1
<i>Dual Stream</i>	Support
<i>Multi-screen display</i>	1/4/6/8/9/10/16/25/36
<i>Resolution</i>	8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 720p, D1, etc.
<i>Trigger Events</i>	Motion Detection, Video Loss, Smart Detection, Human Detection
<i>Sync Playback</i>	1ch 4K, 4ch 1080p, 16ch D1
<i>Search Mode</i>	Smart, Time/Date, Alarm, Smart Detection
<i>Playback Mode</i>	Normal, Motion, Alarm input, Smart Detection
<i>Backup Mode</i>	USB Device, Network
<i>Network Function</i>	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, RTMP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, PPPoE
<i>Remote Users</i>	15 users
<i>Smartphone Connection</i>	Support
<i>Interoperability</i>	SLINK, ONVIF, SDK
<i>HDD</i>	4 SATA interface
<i>Capacity</i>	Up to 16TB for each HDD
<i>Network Interface</i>	2 RJ-45 (10/100 Mbps)
<i>Audio I/O</i>	HDMI Audio Output, 1ch Audio I/O
<i>USB</i>	3 ports (USB 2.0 x 3)
<i>HDMI</i>	1
<i>VGA</i>	1
<i>Operating Conditions</i>	-10°C ~ 50°C
<i>Storage Condition</i>	Less than 90% RH
<i>Certification</i>	CE/FCC
<i>Weight</i>	6 kg without HDD
<i>Dimension</i>	440mm x 355mm x 70mm