

AT-CNS-W100DU

Delegate Unit

DESCRIPTION

AT-CNS-W100DU Delegate Unit Conference is a representative role responsible for participating in conference sessions, facilitating communication between stakeholders, contributing to discussions and decision-making processes, and supporting the achievement of conference objectives. The role involves collaboration with participants from various backgrounds, information exchange, coordination of activities, and active engagement in meetings, workshops, and strategic discussions to promote effective cooperation and organizational development.



MAIN PRODUCT

- Novel and stylish appearance, ergonomic design ,with 2.8 " TFT touch display
- Support discussion ,sign-in,voting,audio tracking functions;
- Uses a dedicated 8-core high-density aviation connector, comes with a 2-meter connecting cable, and a 'T-type' connection mode to ensure reliable connection;
- Cardioid condenser microphone with a built-in speaking indicator light (red when speaking), and is detachable during breaks;
- 12pcs chairman unit is maximum for one system , and its connection location is unrestricted;
- Microphone gooseneck length: 450mm (standard configuration);
- The unit is a passive device, powered by the system host, with an input voltage of DC24V;
- The chairman unit has the ability to forcibly shut down the delegate units of delegates who are currently speaking; it can be freely activated regardless of the number of speakers or speaking mode, and is not limited by installation location;

CONFERENCE SYSTEM

TECHNICAL SPECIFICATION

<i>Description</i>	<i>Delegate Unit</i>
<i>System Capacity</i>	100pcs mic
<i>Connection maximum</i>	Hand in hand by 8 PIN cable
<i>Power Supply</i>	24V DC by controller U S-200MC
<i>Power Consumption</i>	1.5W
<i>Voice Pickup Distance</i>	20-50cm
<i>THD</i>	<0.05%
<i>S/N Ratio</i>	>75dB
<i>Frequency Response</i>	20Hz-20KHz
<i>Crosstalk Attenuation</i>	>80dB
<i>Indicator</i>	Red round ring indicator light on when microphone on
<i>Gooseneck Length</i>	450 mm
<i>Connector</i>	8 PIN connector
<i>Finish</i>	ABS in black
<i>Dimension</i>	109 ×160 x7 5 mm
<i>Weight</i>	0.7kg